



FIGURE 5 Determining blasting percentages after indocking inspection.

References

- 1 “Coating Failure Analysis Learning Series – Part 3 – Tooke Gage,” KTA Staff, <https://kta.com/kta-university/coating-failure-analysis-part-3/>
- 2 J.F. Fletcher, R. Kattan, “The Problem with Meeting Dry Film Thickness Specifications,” <https://www.elcometerusa.com/The-Problem-with-Meeting-Dry-Film-Thickness-Specifications.html>
- 3 A. Forsgren, “What to do when the DFT of the Primer is below Spec,” *J. Phys. Chem.* (March 2000): pp. 17–26.
- 4 L.S. Vernon, “Understanding the Law to Avoid and Manage Coating Claims,” *J Phys. Chem.* (August 2001): pp. 49–53.
- 5 Corrosionpedia, “Tooke Gauge,” (Edmonton, AB: Corrosionpedia, 2023): <https://www.corrosionpedia.com/definition/4894/tooke-gauge>
- 6 TQC Super PIG III Destructive Paint Inspection Gauge user manual, pp. 6–7.
- 7 Wikipedia, “ImageJ,” <https://en.wikipedia.org/wiki/ImageJ>
- 8 D. Kahneman, O. Sibony, C.R. Sunstein, *Noise: a Flaw in Human Judgment*, (New York, NY: Little, Brown, Spark, 2021): pp. 3–10.

TRAIAN RUS is the technical support and account manager for PPG PMC EMEA in Constanta, Romania, email: traianrus@hotmail.com. He has spent more than 25 years in marine and protective coatings and has been a member of AMPP since 2020. **MP**

REVOLUTIONARY CERAMIC EPOXIES

- Fast drying
- Self-healing
- Easy to apply
- NSF 600 approved
- Proven to withstand the test of time

RELIABLE PROTECTION THROUGH INNOVATIVE COATINGS

SCAN ME



induron.com | 205-324-9584 | info@induron.com